

## Impact Wrench XGT TW001GM201



### Product Description

40V MAX XGT • 3/4" • 1 800 Nm • 0 - 2500 min<sup>-1</sup>

**High torque, brushless impact wrench with three power settings for heavy-duty work**

A powerful, brushless 3/4" drive impact wrench with a fastening torque of up to 1 800 Nm. Three different power settings. Equipped with an LED light for added lighting, this tool is ideal for applications that require high fastening torque. Includes 2 x 4,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Electronic 4 stage impact power selection for added versatility
- ⊙ Reverse Rotation Auto Stop Mode stops after the bolt/nut loosened enough
- ⊙ Twin LED job light x 2 with preglow and afterglow functions
- ⊙ Ergonomically designed handle with rubberized soft grip
- ⊙ 3 modes of reaction time for automatic stop available both in forward and reverse rotation modes
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381721059

### Product Specifications

|   |                       |
|---|-----------------------|
| <b>Drive Square</b>                             | 0.75 "                |
| <b>Tool weight with battery (EPTA)</b>          | 3,9 - 5,1 kg          |
| <b>Battery Voltage</b>                          | 40 V                  |
| <b>Brushless Motor</b>                          | YES                   |
| <b>Vibration Level (3 axes), Fastening Bolt</b> | 18,5 m/s <sup>2</sup> |
| <b>Sound Pressure Level</b>                     | 103 dB(A)             |
| <b>Vibration Uncertainty (K Factor)</b>         | 2,0 m/s <sup>2</sup>  |
| <b>Tightening Capacity High Tensile Bolt</b>    | M10 - M27             |
| <b>Product Dimensions (L x W x H):</b>          | 217 x 94 x 303 mm     |
| <b>Product net weight (new)</b>                 | 3,2 kg                |

|   |   |
|---|---|
| <b>Impacts per Minute (IPM)</b>           | 0 - 1900 / 2200 / 2400 / 2500 min <sup>-1</sup> |
| <b>System</b>                             | XGT 40Vmax/80V max                              |
| <b>Sound Power Level (L<sub>WA</sub>)</b> | 111 dB(A)                                       |
| <b>Max Fastening Torque Impact Drill</b>  | 450 / 840 / 1500 / 1800 Nm                      |
| <b>Max Output Power</b>                   | 700 W   |
| <b>Voltage XGT</b>                        | 1   |
| <b>Tightening Capacity Standard Bolt</b>  | M12 - M36                                       |
| <b>Noise Uncertainty (K Factor)</b>       | 3 dB(A)   |
| <b>Tool Category</b>                      | Screwing and Drilling                           |
| <b>Nut-busting torque</b>                 | 2050 Nm   |
| <b>No load speed</b>                      | 0 - 950 / 1150 / 1400 / 1800 min <sup>-1</sup>  |

#### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

#### More info

<https://makita.ae/product/impact-wrench-xgt-tw001gm201/>